Design Settings

Rainfall Methodology	FSR	Maximum Time of Concentration (mins)	30.00
Return Period (years)	100	Maximum Rainfall (mm/hr)	200.0
Additional Flow (%)	0	Minimum Velocity (m/s)	1.00
FSR Region	England and Wales	Connection Type	Level Soffits
M5-60 (mm)	17.000	Minimum Backdrop Height (m)	0.200
Ratio-R	0.300	Preferred Cover Depth (m)	1.200
CV	0.750	Include Intermediate Ground	✓
Time of Entry (mins)	5.00	Enforce best practice design rules	✓

Nodes

Name	Area (ha)	Cover Level (m)	Depth (m)
1	0.030	10.000	2.200

Simulation Settings

Rainfall Methodology	FSR	Analysis Speed	Normal
FSR Region	England and Wales	Skip Steady State	x
M5-60 (mm)	17.000	Drain Down Time (mins)	240
Ratio-R	0.300	Additional Storage (m³/ha)	0.0
Summer CV	0.750	Check Discharge Rate(s)	x
Winter CV	0.840	Check Discharge Volume	x

Storm Durations

15	30	60	120	180	240	360	480	600	720	960	1440

Return Period (years)	Climate Change (CC %)	Additional Area (A %)	Additional Flow (Q %)
100	30	0	0

Node 1 Lined Soakaway Storage Structure

Base Inf Coefficient (m/hr)	0.00000	Invert Level (m)	7.800	Pit Length (m)	3.200
Side Inf Coefficient (m/hr)	0.25600	Time to half empty (mins)	343	Depth (m)	
Safety Factor	3.0	Ring Diameter (m)	2.400	Inf Depth (m)	
Porosity	0.30	Pit Width (m)	3.200	Number Required	1

Flow+ v10.7 Copyright © 1988-2024 Causeway Technologies Ltd

Results for 100 year +30% CC Critical Storm Duration. Lowest mass balance: 100.00%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
360 minute winter	1	272	9.934	2.134	2.3	13.3341	0.0000	OK

Link Event (Outflow)	US Node	Link	Outflow (l/s)
360 minute winter	1	Infiltration	0.6

Flow+ v10.7 Copyright © 1988-2024 Causeway Technologies Ltd