Technical support: +44 (0) 333 202 6800

Date Published: 01/08/2024

Visqueen HP Tanking Primer, 5L

Features and benefits

- No mixing required - use straight from the tin

Product description

Visqueen HP (High Performance) Tanking Primer is a black elastomeric bituminous priming solution. The product is supplied in a 5 litre tin.

Approvals and standards

- BBA Agrement Certified with Visqueen Self Adhesive Membrane, Visqueen Gas Resistant Self Adhesive Membrane and Visqueen TorchOn Tanking Membrane.
- Visqueen certified with Quality Management System ISO 9001:2015
- Visqueen certified with Occupational Health and Safety System ISO 45001:2018
- Visqueen certified with Environmental Management System ISO 14001:2015

Usage

The primer can be used to prepare a variety of substrates including concrete, metal and masonry. It significantly improves the bond of the applied membrane.

It is designed to prepare surfaces prior to the applications of Visqueen self adhesive membranes and Visqueen TorchOn Tanking Membrane.

System components

- There are no Visqueen system components required for this product

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com

Technical support: +44 (0) 333 202 6800

Date Published: 01/08/2024

Visqueen HP Tanking Primer, 5L

Storage and handling

Visqueen HP Tanking Primer should be stored upright, undercover and in its original packaging. Store away from any sources of ignition at temperatures between 5°C and 30°C.

To avoid the risk of spillage, always store and transport in a secure upright position. The unopened product has a minimum shelf life of 24 months.

Use in a well ventilated space away from any sources of ignition. Keep the container closed when not in use.

Care should be taken when handling the product in line with current manual handling regulations.

Preparation

Inspect concrete surfaces for honeycombed areas and holes, if required bag-rub any irregularities or fill the surface with a suitable filler such as 3:1 mortar mix. All surfaces should be frost free, dry, smooth, clean, and free from oils, grease, condensation and other contamination. Remove areas of laitance.

Concrete substrates must be cured for a minimum 7 days prior to primer application.

Installation

Visqueen HP Tanking Primer can be applied directly from the tin using a brush, or transferred to another suitable container and then applied by roller. Do not pour directly onto the surface.

Apply one coat of Visqueen HP Tanking Primer at a coverage of 6 - 8m^2 per litre depending on the porosity of the surface. The primer will dry in 2 - 8 hours depending upon temperature and the primer should be covered by the membrane within 24 hours.

Usable temperature range

It is recommended that Visqueen HP Tanking Primer is installed above 5°C.

Additional information

The information in this datasheet was correct at the time of publication. It is the user's responsibility to obtain the latest version of the datasheet as it is updated on a regular basis. The information contained in the latest datasheet supersedes all previously published editions.

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com

Technical support: +44 (0) 333 202 6800

Date Published: 01/08/2024

Visqueen HP Tanking Primer, 5L

Property	Value
Colour	Black
Number of coats	1
Coverage rate	6 - 8m^2 per litre
Drying time	2 - 8 hours
Coverage per tin	30 - 40m^2

Health and safety information

Refer to Visqueen HP Tanking Primer safety datasheet (SDS).

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com

Technical support: +44 (0) 333 202 6800

Date Published: 01/08/2024

Visqueen HP Tanking Primer, 5L

About Visqueen

The Visqueen name has long been recognised as one of the leading manufacturers of high quality advanced membrane technologies and design based solutions by specifiers, distributors, builders merchants and contractors throughout the UK and Europe.

For further guidance on the Visqueen services shown below, please refer to the relevant section of the Visqueen website (www.visqueen.com) or contact Visqueen Technical Services on +44 (0) 333 202 6800 or enquiries@visqueen.com

Complete Range, Complete Solution



Structural Waterproofing | Gas Protection | Damp Proof Membrane | Tapes | Damp Proof Course | Stormwater | Vapour Control

Visqueen Technical Support

Visqueen combine an extensive product portfolio with industry leading levels of service and support which includes guidance over the phone, bespoke CAD drawings to help with complex detailing, electronic NBS specifications and access to a dedicated team of highly knowledgeable and experienced field based Technical Support Managers.

Visqueen Technical Support is available to all our customers including architects, specifiers, distributors, builders merchants, contractors and end users. All of our technical team have been awarded the industry recognised qualification Certificated Surveyor in Structural Waterproofing (CSSW).

Visqueen CPD Seminars

The Visqueen Continuing Professional Development (CPD) Seminars provide up-to-date information on changes within Building Regulations/Building Standards and nationally recognised industry guidance affecting damp proofing, water vapour control, hazardous ground gas protection and below ground structural waterproofing.

The one hour seminars have been produced for design specialists within the construction sector and are delivered by our team of Technical Support Managers.

Visqueen Training Academy

Based at our manufacturing facility in Derbyshire, the Visqueen Training Academy is available to support Visqueen customers throughout the UK by providing a wide range of both theory and practical skills related training.

Courses include one day product awareness training for our distributors and builders merchants to help them in their day-to-day jobs, through to intensive two day courses giving detailed hands-on training in the practical skills required for safe and robust product installation.

Heanor Gate Road, Heanor, Derbyshire, DE75 7RG
+44 (0) 333 202 6800 I enquiries@visqueen.com I www.visqueen.com