

## **WINDOWS SPECIFICATION**

### **TECHNICAL SPECIFICATION**

All products in multi-layer Finger Jointed Redwood sections for added stability.

Internally beaded throughout for security.

Factory glazed with argon gas filled double glazed units featuring soft-coat energy saving glass.

Drained and vented sections to protect against sealed unit failure.

Fully factory finished with high performance, micro-porous paint treatments.

### **SIZE SPECIFICATIONS**

|                 |                                   |
|-----------------|-----------------------------------|
| Cill            | 145mm x 38mm (inc. in overall ht) |
| Frame Head Size | 75mm                              |
| Height          | 915mm                             |
| Size Of Bar     | 36mm                              |
| Width           | 610mm                             |

### **TECHNICAL SPECIFICATIONS**

|                        |                          |
|------------------------|--------------------------|
| Cill Species           | Finger Jointed Redwood   |
| External Grille Colour | White - RAL 9003         |
| FSC® Certified         | Yes                      |
| Feature Mould          | Ovolo                    |
| Glass Pattern          | Clear                    |
| Glass Type             | 4mm Annealed (24mm Unit) |
| Glazing Features       | Horizontal Astragal Bars |
| Head Drip              | Yes                      |
| Style Option           | Dummy Sash               |
| Trickle Vent Location  | Head of Frame Trickle    |
| Vent Quantity          | 1                        |
| Trickle Vent Size      | EA 3000                  |