

DOOR SCHEDULE - CHARWOOD					WALL TYPES										PRINTED				
REF	TYPE	HEIGHT	WIDTH	COMMENTS	EXTERNAL WALL BRICK OR RENDER ON LAY LITE BLOCK OUTER LEAF - 150MM CAVITY FILLED WITH SUPERAIR INSULATION R-0.033. 100MM THICKNESS THURCO BLOCK, PLASTERBOARD ON INNER LEAF. VALUE = 0.18 W/M2.										REV	DESCRIPTION	DATE	BY	CHK
00 - GROUND FLOOR					PARTY WALL (E-WM-20) 120MM FILLED CAVITY WITH EACH SIDE - 100MM ROCKWOOL - 12.5MM PLASTERBOARD ON DWS WITH SMUSH FINISH										P1	FIRST ISSUE	25/01/2024	DP	SP
D5	INT SINGLE	2110	920		INTERNAL LOADBEARING WALL (DEER TO ENGINEERS DETAILS) 100MM ROCKWOOL & 12.5MM PLASTERBOARD ON DWS WITH SMUSH FINISH BOTH SIDES														
D6	INT SINGLE	2110	900		INTERNAL NON-LOADBEARING WALL - FIBRE STUDS (75X80 @ 600MM) INDICATED - 150MM FOAM ACOUSTIC INSULATION (HOLL) (ONLY WHERE INDICATED)														
D7	INT SINGLE	2110	900		WALL FINISHED ROTIC WITH TWO LAYERS OF 12.5MM PLASTERBOARD AND SMUSH FINISH UNLESS LATED														
D8	INT SINGLE	2110	920																
D9	INT SINGLE	2110	920																
XD1	ExtSgl IG XD63	2110	1023																
XD2	Door_Sliding patio, External	2110	1473																
XD3	ExtSgl IG XD63	2110	1023																
XD4	Garage - Horz Pnl	2250	2260																
01 - FIRST FLOOR																			
D10	INT SINGLE	2110	920																
D11	INT SINGLE	2110	824																
D12	INT SINGLE	2110	920																
D13	INT DOUBLE	2110	910																
D14	INT SINGLE	2110	920																
D15	INT SINGLE	2110	768																
D16	INT SINGLE	2110	920																
D17	INT SINGLE	2110	920																
D18	INT SINGLE	2110	824																
NOTE: BACKGROUND VENTILATION TO BE 8000 SQ MM TO HABITABLE ROOMS, 4000 SQMM TO BATHROOMS AND UTILITIES WHICH IS TO BE PROVIDED BY THE WINDOW AND EXTERNAL DOOR TRICKLE VENTS. GROUND FLOOR DOORS TO HABITABLE ROOMS AND ROOMS CONTAINING A WC TO HAVE A MINIMUM CLEAR OPENING OF 800MM WHEN NOT APPROACHED HEAD ON AND 750MM FINISHED GAP AT THE BOTTOM TO PROVIDE REQUIRED BACKGROUND VENTILATION (PROVIDE A 20MM UNFINISHED GAP WHERE FINISHES ARE NOT LAID). ALL CYLINDER DOORS TO BE VENTED EQUIVALENT TO 600MM2. ALL WINDOWS AND DOORS SHALL BE PROVIDED AND MECHANICALLY FIXED TO MEET THE SECURITY REQUIREMENTS OF PAS 54:2016																			