



BOL301 Bollard

Straight to mains, IP65, 500lm bollard

Features

IK rating	IK08
IP rating	IP65
CSP Switchable	Fixed colour
LED Lifetime	30,000h L70
CRI	80 Ra
SDCM	4 SDCM

Installation information

UK Bathroom Zone	2
Inrush Current	20A
Construction Material	Aluminium / PVC
Weight	4.6Kg
Maximum Ambient Temperature	40°C
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
BOL301X30	Black RAL9011	23W	3000K	360°	500	22	144

Wiring information

Cable Required for Connector	3x 1.0mm ²
Type of Wiring Required	Parallel

LED driver

N/A (Integrated SLEV driver)	220-240V	Yes	No	-	N/A	N/A
------------------------------	----------	-----	----	---	-----	-----

Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	--	-----------------



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting


Guarantee

5 year extended warranty

Features & benefits

- 23W
- IP65 ideal for car parks and walk ways
- Black powder coated finish
- Straight to mains screw terminals
- Domed top for a low glare finish, and a minimum up spill of light making it comfortable on the eye
- Comes complete with root mounting kit
- Benefiting from light all round with a 360° beam angle

Beam angle: 360°



Ø150mm

