

Road Marking Reference Schedule					
TSRGD REF	Description	Width (mm)	Module (mm)	Length (mm)	Text Height (mm)
1003A	Yield line	-	-	-	-
1004	White lane markings/centre line	100	6000	4000	-
1009A	Edge of carriageway	100	900	600	-
1023A	Yield triangle	-	-	-	-
1024	Slow marking	-	-	-	1600
1035	Traffic lane destinations	-	-	-	1600
1038	Traffic lane manoeuvre arrows	-	-	4000	-
1040	Hatching: Two way travel either side	100	6000	4000	-

Sign Reference Schedule					
TSRGD REF	Description	Size	Post & Foundation	Location	x-Height
506.1	Junction ahead (left/right)	600	76mm CHS Post 350x350x600mm ST5 Foundation	75 yds east & west of junction centre	n/a
7014(d)	"TREFN FFYRDD NEWYDD O'CH BLAEN NEW ROAD LAYOUT AHEAD" Welsh over English	750(w) 600 (h)	89mm CHS Post 450x450x800mm ST5 Foundation	100 yds east & west of junction centre	37.5
670	40mph repeater (eastbound & westbound)	300	N/A 350x350x600mm ST5 Foundation	every third lamppost every 100yds at back of footway on northside of carriageway after end of new lampposts to former Croes Howell Restaurant & Bar	n/a
670	40mph	600	N/A attached to existing posts replacing national speed limit signs	former Croes Howell Restaurant & Bar & Crown Crossroads	n/a

DIAG. 506.1 PLACED 75 YDS EITHER SIDE OF THE JUNCTION ON SIDE OF ONCOMING TRAFFIC



DIAG. 7014 (d) 'TREFN FFYRDD NEWYDD O'CH BLAEN NEW ROAD LAYOUT AHEAD' (WELSH OVER ENGLISH) PLACED 100 YDS EITHER SIDE OF THE JUNCTION ON SIDE OF ONCOMING TRAFFIC CONTRACTOR TO REMOVE 6 MONTHS AFTER FIRST OCCUPATION OF THE DEVELOPMENT



DIAG. 670 '40' mph REPEATERS ATTACHED TO EVERY THIRD NEW LAMP POST FACING EASTBOUND & WESTBOUND TRAFFIC FROM CROWN CROSSROADS JUNCTION AND THEN ON INDIVIDUAL POSTS AT 100yd INTERVALS TO 30mph LIMIT CHANGE AT THE FORMER CROES HOWELL RESTAURANT & BAR. EXISTING NATIONAL SPEED LIMIT SIGN FOR WESTBOUND TRAFFIC @ CROES HOWELL TO BE CHANGED TO DIAG. 670 '40' mph EXISTING NATIONAL SPEED LIMIT SIGN FOR EASTBOUND TRAFFIC @ CROWN CROSSROADS TO BE CHANGED TO DIAG. 670 '40' mph



WEEBOL RETROFLECTIVE BOLLARDS

WEEBL RETROFLECTIVE BOLLARDS

GENERAL NOTES:

- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT ARCHITECTS AND ENGINEERS DRAWINGS AND SPECIFICATIONS.
- DO NOT SCALE THIS DRAWING. ANY AMBIGUITIES, OMISSIONS AND ERRORS ON DRAWINGS SHALL BE BROUGHT TO THE ENGINEERS ATTENTION IMMEDIATELY. ALL DIMENSIONS MUST BE CHECKED / VERIFIED ON SITE.
- ALL DIMENSIONS ARE IN METRES UNLESS NOTED OTHERWISE.
- FOR GENERAL NOTES REFER TO DRAWING.

KEY

- B* Bollard incorporating diagram 610
- Dia. XXXX Refer to 'Road Marking Reference Schedule' on drawing and TSRGD 2016 for detail of road markings
- S278 Boundary. Civils Works.

REFER TO HARTTRON DRAWINGS 20020-D-01, D-02 & D-03 FOR DETAILS OF NEW STREET LIGHTING SCHEME

C05	UPDATED TO REMOVE MARKINGS AS PER RSA 1/2	12/03/20	RM	RM
C04	AS SHOWN	18/02/20	MF	RM
C03	SIGNAGE REQUIREMENTS AMENDED	07/02/20	MF	RM
C02	HATPIN BOLLARD NOTES & BOUNDARY UPDATED	06/01/19	MF	RM
C01	ISSUED FOR S278 APPROVAL	27/11/18	MF	RM
Rev:	Description:	Date:	By:	Chkd:



Merchant Exchange, 17-19 Whitworth Street West, Manchester, M1 5WG
0161 235 2394
manchester@curtins.com
www.curtins.com

Civils & Structures • Transport Planning • Environmental • Infrastructure • Geotechnical • Conservation & Heritage • Principal Designer
Birmingham • Bristol • Cambridge • Cardiff • Douglas • Dublin • Edinburgh • Glasgow • Kentish • Leeds • Liverpool • London • Manchester • Nottingham

Status: **ISSUED FOR CONSTRUCTION APPROVAL**

Project: **GRESFORD ROAD LLAY**

Orig Title: **STRAIGHT MILE GIRT ROAD MARKING AND SIGNS**

Size:	Date:	Drawn By:	Designed By:	Checked By:
A1	11/10/2018	MF	MF	RM
Scale:	1:250			
Project No:	Originator:	Zone:	Level:	Type:
065665	CUR	ZZ	XX	DR
D	D			
9504				
C05				