

MEMORANDUM



From: Chief Officer, Environment & Technical **To:** Chief Officer Planning & Regulatory
Our Ref: ET/DC/2022/0125 **Your Ref:** SB/P/2022/0125
Date: 07th March 2022

TOWN AND COUNTRY PLANNING ACT 1990

FFURFIO MYNEDFA I GERBYDAU / FORMATION OF VEHICULAR ACCESS **17 ERW WLADYS GLYN CEIRIOG WREXHAM**

Grid Ref: E 320394 N 338180

Erw Wladys, is classified and subject to a 30mph speed limit, the visibility splay required would be 2.4m x 43m, measured in both directions to the nearside edge as per Manual for Streets. the actual speed limit will probably be lower than the posted speed limit. In this instance we would estimate the actual speed to be 25mph and require a 2.0m x 33m visibility splay.

The submitted plan shows the proposed parking arrangement provides dimensions of 3.2m access width and 6.5m length. Minimum standard parking space dimensions as per Manual for Streets (*length 4.8m / width 2.4m*).

By providing off street parking and maximizing the visibility this would be a significant improvement.

If the application is supported, then I would recommend that the applicant applies for s.184 consent to lower the kerb to form a suitable access (see note).

I recommend that any permission include the following conditions:

CONDITIONS

ZJ09 NO GATES WITHIN 5 METRES

033R There shall be no gates or other means of enclosure across the vehicular access point within 5 metres of the highway boundary.

ZJ07 ACCESS SURFACE (5 metres)

043R Prior to first use of the vehicular access hereby approved, the access shall be surfaced with hard bound materials (e.g. bituminous macadam) for a minimum distance of 5 metres behind the adjoining highway.

ZJ46 NO PRIVATE SURFACE WATER RUN OFF

026R No private surface water run off shall be permitted to flow from the development site onto the adjoining highway. An Aco drain or similar shall be provided across the approved access to intercept any such run off prior to first use of the development.

- ZJ11
039R** **ACCESS WIDTH**
The vehicular access hereby approved shall be a minimum width of 3.2 metres
- ZJ13
026R
E05NA** **DROPPED KERB VEHICULAR CROSSING**
The vehicular access(es) hereby approved shall take the form of a dropped kerb vehicular crossing.
- ZJ09
033R** **NO GATES WITHIN 5 METRES**
There shall be no gates or other means of enclosure across the vehicular access point within 5 metres of the highway boundary.
- ZJ13
026R
E05NA** **VISIBILITY SPLAYS IN BOTH DIRECTIONS (NEAR SIDE)**
Prior to first use of the development hereby approved the vehicular access shall provide visibility splays of 2.0 metres x 33 metres in both directions measured to the nearside edge of the adjoining highway. Within these splays there shall be no obstruction in excess of 1 metre in height above the level of the nearside edge of the adjoining carriageway. The splays shall thereafter be permanently retained clear of any such obstruction to visibility.

Supplementary Notes

The applicant's attention should be drawn to item nos. 1, 3, 4 & 5 of the supplementary notes.

Note to Applicant

A licence should be obtained (as required by section 184 of the Highways Act 1980) from the Highway Authority in order to lower the kerbline and cross the footpath at the new access position. Further guidance can be obtained from the Highways Department of Wrexham County Borough Council on telephone 01978 729670.



Chief Officer, Environment & Technical