

Tamlite Lighting

TC Lighting Columns

Light duty steel lighting column

Product Data Sheet



- Features:**
- Hot dipped galvanised to Bs729
 - Traditional tubular style with semi-flush door
 - Full range of brackets and spigots available
 - High quality mild galvanised steel
- Construction:**
- High quality mild galvanised steel
 - Designed to Bs 5649 series 1300
 - Root section externally bitumen coated
 - Primed versions available at extra cost for on site painting after installation
- To Specify / Order:**
- Steel, tubular galvanised steel lighting column as per Tamlite TC range
- Options:**
- NOTE: Wind speed and environmental conditions vary greatly within the British Isles mainland. It is therefore vital to consult with Tamlite Technical to obtain correct advice on column selection
- FP Flange plate. Please contact Tamlite Technical for full details



Order Codes

All dimensions are in millimetres

Order Code	Availability	Wgt (kg)	Mounting height (m)	Planting depth	Shaft O/D
TC3M		28	3.0M	600	76
TC4M		33	4.0M	600	76
TC5M		40	5.0M	600	76
TC6M		51	6.0M	600	76

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.



Tamlite Lighting Technical Department.
Tel: 01952 292441 Fax: 01952 292155
e-mail: technical@tamlite.co.uk