



KEY	
	HEDGEROW
	EXISTING VEGETATION TO REMAIN
	EXISTING TREES
	PROPOSED PLANTED AREAS
	GRAVEL - LIMESTONE CHIPPINGS

GROUND COVER PLANTING			
3 per m2			
Species	Size	Type	No.
Hedera helix 'Glacier'	30-40cm	P9	40.5
Vinca major	30-40cm	P9	40.5
TOTAL			
HEDGEROW PLANTING			
5 per lin m (double staggered row)			
Species	Size	Type	No.
Ligustrum vulgare		0 bare root	16

- PLANNING NOTES
- Plant handling at the nursery, and during transit up to delivery, shall be in accordance with 'Plant Handling' the booklet published by the Committee for Plant Supply and Establishment (CPSE). The contractor shall comply with clauses 3 & 4 of the above booklet (obtained from the Horticulture Trades Association) which refers to the receipt, unloading and temporary storage of plants.
 - Plants shall be first class examples of their species or variety, free from all pests and diseases with good fibrous root systems and materially undamaged. (Refer to relevant sections of BS3936 Parts 1-4 'Specification of Nursery Stock')
 - All planting is to be in general compliance with BS4428: 1989 'Code of Practice for general landscape operations (excluding hard surfaces)'.
 - The contractor must ascertain for himself the exact location of any underground services and maintenance points.
 - Prior to planting areas to be planted shall be sprayed off to remove vegetation.
 - At the time of planting and seeding areas will have topsoil prepared to an approved depth: -
 - Topsoil to planting areas (within plant beds) to be 400mm deep
 - Topsoil to grass areas to be 150mm deep
 - Hedgerow trenches to be 400mm wide x 300mm deep
 - Plants shall be planted in groups of 3-7no.
 - Water as necessary to ensure the establishment and continued thriving of planted and grassed matter.
 - Carry out all work when soil and weather conditions are suitable:
 - Do not plant during periods of frost or strong winds. Plant only during the following periods: -
 - Bare root deciduous trees and shrubs: Late October to late March
 - Container grown plants: At any time if ground water and weather conditions are favourable.
 - All planted areas to be mulched to a consolidated depth of 75mm using an approved amenity grade bark mulch
 - Ensure that litter picking and weed control is regularly carried out.

Project:		TURNPIKE HOUSE	
Drawing Title:		GARAGE LANDSCAPE PROPOSAL	
		Scale: 1:200@A3	
		Date: 03/06/20	
		Drawn By: OB	
		Drawing No. : LD01	Rev: A

Contractors are advised to check dimensions with the architect before setting out on site