



- Sanderson Associates (Consulting Engineers) Ltd ("the consultant"), has not checked or verified, and shall have no liability whatsoever for any inaccuracies which may be attributable to any data, reports, base plan(s) and drawings provided by the client, or purchased by the consultant on the client's behalf, that may have been utilised within this drawing.
- The consultant shall not be liable for the use by any person of any document for any purpose other than that for which the same were provided by the consultant.
- No liability whatsoever is accepted by the consultant for any error or omissions.
- The consultant accepts no liability for any vehicle specification errors within the vehicle track software used and / or it's vehicle libraries.
- The locations of utilities apparatus, if shown, is reproduced from plans supplied to the consultant, although care has been taken when duplicating this information. These locations are approximate only and no guarantee can be given for their accuracy. It is the clients or it's appointed agent/contractors responsibility to verify the exact locations on site by hand dug trial holes or other appropriate means prior to mechanical excavation.
- Service connections are not shown but their presence should be anticipated.
- Reference to any third party equipment shown on this drawing was only relevant at the time the drawing was prepared.
- It is the client's responsibility to ensure that any equipment ordered meets the design.

KEY:

Proposed Full Depth Carriageway Construction

40mm SMA 10 Surf 70/100
90mm AC20 Binder
150mm Type 1 Granular Sub Base
200mm 30% CBR Layer Re-engineered Material

Proposed Full Depth Carriageway Construction Suitable for HGV Traffic

40mm SMA 10 Surf 70/100
150mm AC20 Binder
150mm Type 1 Granular Sub Base
200mm 30% CBR Layer Re-engineered Material

Proposed Carriageway Construction

Concrete slab by others. Specification to be confirmed by Structural Engineer

Proposed Full Depth Parking Bay Construction

40mm SMA 10 Surf 70/100
60mm AC20 Binder
150mm Type 1 Granular Sub Base
200mm 30% CBR Layer Re-engineered Material

Footway Construction

60mm - Concrete block paviors with pencil edge laid stretcher bond
35mm - 3:1 sand cement screed
100mm - ST4 concrete

Footway Construction

25mm - 0/6mm DBM 190 pen red surface course in lime stone
55mm - 0/20mm DBM 190 pen binder course in lime stone
150mm - Type 1 Sub-Base clause 803

Footway Construction

25mm - 0/6mm DBM 190 pen surface course in lime stone
55mm - 0/20mm DBM 190 pen binder course in lime stone
150mm - Type 1 Sub-Base clause 803

Landscaping

150mm Topsoil and seed

A	Amended to suit revised site layout 181161-PL-04d	LM	28.01.19	PJM
Rev	Amendment	Drawn	Date	Checked

PRELIMINARY
DRAWING

sanderson
associates
(consulting engineers) ltd

Highways | Traffic | Transportation | Water

T 01924 844080 mail@sandersonassociates.co.uk
F 01924 844081 www.sandersonassociates.co.uk

Client	EURO GARAGES LTD		
Project Title	HOLT ROAD, WREXHAM		
Drawing Title	PROPOSED PAVEMENTS		
Scale	1:250	Drawn By	LM
Drawing Size	A1	Checked By	PJM
Date	17.12.18	Approved By	PJM
	Drawing Number 10802/700/001	Rev	A