



LED Bollard II

BCP151 LED150/WW PSU 220-240V 9006

LED Low Power - 830 warm white - Power supply unit - 220 to 240 V

People want to create a pleasant atmosphere around their property – something that will catch visitors' attention, make them feel good and want to come back again. They would like to be able to create an appealing ambience with optimized-quality lighting at minimum cost. Combining reliable low-power LEDs and an integrated driver, the robustly designed LED Bollard II delivers an affordable LED lighting solution to meet your landscaping needs.

Product data

General Information	
Number of light sources	1 pc
Lamp family code	LED-LP [LED Low Power]
Light source color	830 warm white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover UV-resistant
Embedded control	-
Connection	Screw connection block
Cable	Cable without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
Warranty period	1 years
RAL color	White aluminum (9006)
Constant light output	No
Number of products on MCB of 16 A type B	1

Light source engine type	LED
--------------------------	-----

Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Power Factor (Min)	0.4

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover/lens material	Polycarbonate
Mounting device	Baseplate
Optical cover/lens finish	Matte
Overall height	800 mm
Overall diameter	180 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
-------------------------	---


LED Bollard II

Mech. Impact protection code	IK10 [20 J vandal-resistant]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	150 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	21.43 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial input power	7 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-20 to +40 °C

Product Data	
Full product code	910403308302
Order product name	BCP151 LED150/WW PSU 220-240V 9006
EAN/UPC - Product	8710163278940
Order code	910403308302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910403308302
Net Weight (Piece)	1.850 kg



Dimensional drawing



LED Bollard II BCP150/151

