MH No.	MANHOLE DETAILS							COVER DETAILS					PIPE DETAILS				LAYOUT	REMARKS	COORDINATES
	Internal Size	Type			Levels		Depth (m)	Grade of Cover			BS EN124 Cover Ref.	Cover Size Clear Opening	Type of Pipe	Size In	Size Out	Invert Level			
		Brick	Conc	Poly	Cover	Invert		D	C	B									
SA 1.0	2100Ø		✓		23.000	20.500	2.500			✓	B125	675x675	uPVC	150a		21.305		SOAKAWAY	
													uPVC	150b		21.305		630mm SURROUND	
SA 2.0	1800Ø		✓		22.400	20.400	2.000			✓	B125	675x675	uPVC	150a		21.640		SOAKAWAY	
																		540mm SURROUND	

NOTES

1. This drawing is to be read in conjunction with all relevant Engineers drawings, Architects drawings and Specifications.
2. Cover levels to new manholes are estimated and are to be coordinated on site with the proposed finished levels / details.
3. Safety chains to be provided for outgoing pipes greater than 600mmØ.
4. Rocker pipes to be provided at entry & exit of manholes for all pipes of 750mm diameter and less.
5. All manholes shall be watertight.
6. All invert levels relate to the centre of the manhole.

A1	SOAKAWAY SIZES AMENDED	GNT	NOV '15

OPUS
Wrexham Office
+44 1978 368100
Opus House, Yale Business Village
Wrexham Technology Park,
Wrexham LL13 7YL

Drawn	Designed	Approved	Revision Date
JR	JR	WJG	NOV '15

Project No.	Scale
V-R6280	

Project
RESIDENTIAL DEVELOPMENT
FORMER ATS GARAGE, MARFORD

Sheet
PROPOSED SOAKAWAY
SCHEDULE SHEET

Drawing No.	Sheet No.	Revision
V-R6280.00/50/CL	006	A1