



Site Plan

Plot	Required Attenuation, dB(A)		Glazing		Ventilation	
	Living Rooms (LR)	Bedrooms (Bed)	LR	Bed	LR	Bed
1 & 2	22	21*	2	2	A	B
3	21	14*	2	2	B	B
4, 5, 6 & 7	19	12*	2	2	B	B
8 & 9	21	14*	2	2	B	B
Flats	21	14*	2	2	B	B

* indicates specification is controlled by LAmax, levels rather than LAeq,T for the period

Glazing Option 1 - 10mm glass/12mm air space/6mm glass
 Glazing Option 2 - Conventional double-glazed unit
 Ventilation Option A - Acoustically treated trickle ventilators
 Ventilation Option B - Conventional trickle ventilators

Provide close boarded timber fencing in positions as indicated.
 Fencing to be 2m in height and have a mass of no less than 15kg/m² (e.g. 19.5mm timber) to achieve an effective acoustic barrier.

Rev	Date	Detail	Initial
B	05/13	Acoustic Specifications	D.J.E.
A	04/13	Acoustic Specifications	S.M.E.

Project:
 Proposed residential
 Development on
 Land at Moreton Avenue
 Johnstown

Title: Site Plan
 Scale: (A3)
 1:500

Drawn By: S M Eltham
 Date: Mar 2013

Drawing No: NO06/32
 Sheet: 1 of 1

blueprint
 architectural services



Redwither Business Centre,
 Redwither Business Park,
 Wrexham. LL13 9XR
 Tel: 01978 356500
 www.blueprintarchitectural.com