



★ Base Plate and Headplate fixing positions:
 10 fixings to floor using ScrewTite Prodrive
 6 x 120mm Screws or equivalent;
 10 fixings to ceiling using ScrewTite Prodrive
 6 x 80 mm Screws or equivalent.
 Note: More fixings are required to a non-self
 supporting wall.

Fixing of studding and noggings -
 Use BAT Framing Anchors Types
 BL- and C or equivalents.
 Protective non-adhesive
 foam gasket:
 Advance Materials Ltd
 Section 2969 15 mm x 80 mm.
 Fix to new wall studs prior to
 fixing installation.

Fixing Details 1:20

Client: Mr & Mrs Wright Address: Trevaylyn Court, Rossett, Wrexham, LL12 0HH	Site Address: Trevaylyn Court, Rossett, Wrexham, LL12 0HH	NOTES: Wall linings: 15mm SoundBloc and wood panelling, Panels, mouldings and beading shall match/hammonise existing. Fill the partition cavity with 100 mm Insulation.	Amendments Date Details
Project: Installation of Partition wall to create a new bedroom area.	Drawing: Proposed Fixing Details	Issue Date: 03/12/12 Drawn by: RG	Drawn by:
Job No: 1224-12	Scales: 1 : 20		

Roland George & Associates:

Roland George MRICS FCIQB FASI
 Chartered Surveyor - Architectural Consultancy
 Residential - New Build - Conversions - Renovation
 Listed Buildings - Refurbishment - Light Commercial
 Phone: 01778 844078
 Email: rgeorge@property-surveyor.co.uk
 Rhodanearchrog
 Wrexham LL14 1AS

Information contained in this drawing is provided in
 good faith with due regard to accuracy, and with no
 intentional infringement of 3rd party copyright.
 Check all dimensions on site and in the
 event of discrepancy notify Roland George
 (Chartered Surveyor) and cease work
 in the area of the discrepancy until
 it is resolved.
 All rights reserved.

Dwg No: 122404
 Issue Date: 03/12/12