ofgem Making a positive difference for energy consumers

Non-Domestic Renewable Heat Incentive

www.ofgem.gov.uk/ndrhi

22 JUN 2018

Emissions Certificate

In order to accredit any biomass boiler or stove applications received for the domestic or non-domestic Renewable Heat Incentive (RHI) schemes, Ofgem must be satisfied that a valid emissions certificate exists for the specific model in the application (or alternatively for the non-domestic RHI, an environmental permit for the site). This template incorporates all information required to demonstrate that the tested plant meets the air quality requirements of the RHI. It must be fully completed and issued by a testing laboratory in order to be a valid certificate.

1. TEST HOUSE	
a) Name and address of the testing laboratory that has carried out the required tests and issued this certificate * **if different, include details of both*	BLT HBLFA Francisco Josephinum Wieselburg HBLFA Francisco Josephinum BLT Wieselburg AT 3250 Wieselburg, Rottenhauser Straße 1 blt@josephinum.at, http://blt.josephinum.at
b) Name and signature of the person authorised by the testing laboratory to issue the certificate	Name: Franz HANDLER (For the test institute) Signature [redacted] Name: Josef RATHBAUER (For the factual* Signature [redacted] Forschungsanstalt * Wieselburg
c) Date of issue of this certificate, together with certificate reference number for this certificate **Please see Note A*	Date: 04/08/2020 Certificate reference number: BLT 0277/20 *Optional:* reference number of original test report on which this certificate is based:
Plant 1: ETA eHack 120 Plant 2: ETA eHack 240 *Type-tested boilers (2g):* ETA eHack 140 (family member) ETA eHack 150 (family member) ETA eHack 160 (family member) ETA eHack 170 (family member) ETA eHack 180 (family member) ETA eHack 200 (family member) ETA eHack 220 (family member)	BLT Test report, approval no: 004/18 BLT Test report, approval no: 041/19 BLT reference number: 0230/19 BLT reference number: 0230/19 BLT reference number: 0230/19 BLT reference number: 0230/19 BLT reference number: 0230/19 BLT reference number: 0230/19 BLT reference number: 0230/19
d) If the testing laboratory that has carried out the required tests is accredited to BS EN ISO/IEC 17025:2005, date of accreditation and accreditation number *(if testing conducted on or after 24 September 2013, the testing laboratory **must be** BS EN ISO/IEC 17025:2005 accredited at the time of testing)*	Date: 21/02/2019 Initial date of accreditation: 01/09/1998 Accreditation number: A 0112 Federal Ministry for Digital and Economic Affairs Division I/12 – Accreditation Body

2. PLANT - *Please see Note B*	**Plant 1**	**Plant 2**
a) Name of the plant tested	ETA eHack 120	ETA eHack 240
b) Model of the plant tested* **Please ensure this is the same as in the manufacturer's documentation and boiler nameplate*	Chipped wood heating boiler ETA eHack 120	Chipped wood heating boiler ETA eHack 240
c) Manufacturer of the plant tested	ETA Heiztechnik GmbH Gewerbepark 1 AT 4716 Hofkirchen	
d) Installation capacity* of the **tested** plant in kilowatts (kW) **The total installed peak heat output capacity*	119,9	238,0
e) Is the plant a manually stoked, natural draught plant? (without a fan providing forced or induced draught)	no	no
f) (i) Date the plant was tested* (ii) Please confirm that NOx and PM have been tested on the same occasion **This is in reference to the emissions testing for PM and NOx, not any wider range of tests. A specific date is required. Please provide the date of test performed at ≥85% of the installation capacity.* *If more than one model has been tested or testing has been conducted on different dates for different fuels, please list each date with details.*	16/11/2017 yes	15/02/2019 yes
g) Please list all the plants in the type-testing range* of the tested plants to which the certificate applies, if any.[1] Please include the **installation capacity** of each model. **This must follow the ratio rules:* *If the smallest plant in the range is 500kW or less, the largest plant in the range can't be more than double the smallest.* *If the smallest plant in the range is over 500kW, the largest plant in the range can't be more than 500kW greater than the smallest.*	Chipped wood heating boiler ETA eHack 120 (119,9 kW) ETA eHack 140 (139,9 kW) ETA eHack 150 (149,9 kW) ETA eHack 160 (159,9 kW) ETA eHack 170 (169,9 kW) ETA eHack 180 (179,9 kW) ETA eHack 200 (199,9 kW) ETA eHack 220 (219,9 kW) ETA eHack 240 (238,0 kW)	

[1] The type-testing approach enables testing laboratories to provide assurance that all boilers in a given range meet the air quality requirements, without needing to specifically test each boiler.

3. FUELS	
a) Types of fuels used when testing *(Where relevant, the fuel should be classified according to EN303-5, referencing the relevant EN14961 standard for **specific classification** (superseded by EN ISO 17225). We don't expect broader categories such as 'beech'.*	Wood Chips A1 (EN ISO 17225-4:2014)
b) Based on the testing, list the range of fuels that can be used in compliance with the emission limits of 30 grams per gigajoule (g/GJ) net heat input for particulate matter (PM), and 150 g/GJ net heat input for oxides of nitrogen (NOx) *(Where relevant, the fuel should be classified according to EN303-5, referencing the relevant EN14961 standard for **specific classification** (superseded by EN ISO 17225). We don't expect broader categories such as 'beech'.*	Wood chips according to - EN 303-5: 2012, class B1 - EN ISO 17225-4:2014, class A1, 15% up to 25 % moisture - EN ISO 17225-4:2014, class A2, 15% up to 35 % moisture Wood chips Grade A according to BSI PAS 111 *)
c) Moisture content of the fuel used during testing. (If multiple fuel types have been tested state all.) Plant 1: ETA eHack 120 Plant 2: ETA eHack 240	Wood chips 16,5 % 15,5 %
d) Maximum allowable moisture content* of fuel that can be used with the certified plant(s) that ensures RHI emission limits are not exceeded. **This value may be obtained from ranges specified in relevant EN14961 standard for specific fuel classifications or EN303-5 when not applicable. Different fuel types should state different maximum allowable moisture contents.*	Wood chips according to: - EN 303-5:2012: class B1, 35 % - EN ISO 17225-4:2014, class A1, 25 % - EN ISO 17225-4:2014, Class A2, 35 % Wood chips Grade A according to BSI PAS 111: 35 %

*) Based on analysis of the accredited laboratory BLT the composition of the tested fuel, chipped wood, Grade A according to PAS 111:2012 meets the requirements of graded wood chips, class B2 according to EN ISO 17225-4:2014, and wood chips, class B1 according to EN 303-5:2012. Further requirements f.e. any need of an environmental permit for using waste wood are not handled in this certificate.

4. TESTS	
Confirm which requirements the emissions of NOx and PM have been tested in accordance with. **Either 4a or 4b must be confirmed to be a valid RHI certificate.**	
a) **Was the testing carried out in accordance* with all of the provisions relevant to emissions of PM and NOx in either BS EN 303-5:1999 or BS EN 303-5:2012?**[2] **It is **not** a requirement that the tested plant must be within the scope of one of these standards, as long as the test lab can confirm that **all of the relevant provisions** were followed appropriately*	yes (EN 303-5:2012)*)
b) **Was the testing carried out in accordance with all of the following requirements?** (i) - EN 14792:2005 in respect of NOx emissions - EN 13284-1:2002 or ISO 9096:2003 in respect of PM emissions[3] (ii) emissions of PM represent the average of at least three measurements of emissions of PM, each of at least 30 minutes duration (iii) the value for NOx emissions is derived from the average of measurements made throughout the PM emission tests.	 Tested according to 4a Tested according to 4a Tested according to 4a Tested according to 4a
c) Please confirm the plant was tested at ≥85% of the installation capacity of the plant.	yes
d) Please confirm the test shows that emissions from the plant were no greater than 30 g/GJ PM and 150 g/GJ NOx.	Yes
e) Measured* emissions of PM in **g/GJ** net heat input **This average value should be from the test confirmed in 4c* *Results from partial load tests are not required.* *This value must be in the specified units.* Plant 1: ETA eHack 120 Plant 2: ETA eHack 240	 10 8
f) Measured* emissions of NOx in **g/GJ** net heat input **This average value should be from the test confirmed in 4c.* *Results from partial load tests are not required.* *This value must be in the specified units.* Plant 1: ETA eHack 120 Plant 2: ETA eHack 240	 54 51

*) All the tests have been carried out according the requirements of the EN 303-5:2012 except the moisture content of the wood chips. In EN 303-5:2012 the stated moisture content for the test fuel for B1 wood chips is from 20 till 30 %. The used test fuels had a slightly lower

[2] BS EN303-5:1999 and 2012 explain what should be measured and when.
[3] These standards explain how to make the PM and NOx measurements.

moisture content (16,5 and 15,5 %). This has no influence on the stated emissions values for PM and NO_x. The confirmation under 4 d) is correct.

Note A: If details from a previously issued certificate or an original test report are being transferred to this RHI emission certificate template, please note that this document must be **issued by the testing laboratory** as a separate certificate. The issue date and certificate reference number should be in relation to *this* certificate produced using the RHI template, not the issue date and reference number of the original certificate or test report.

Note B: If you are including multiple tested plants on one certificate, please ensure that all sections are completed for each tested plant, and are laid out such that it is clear which details relate to which tested plant. If a type-testing range is included as well, please show clearly which type-testing range relates to which tested plant(s), following the type-testing range ratio rules outlined in 2g.